



Netherlands Collection Specifications

This fully customizable collection truly highlights the natural state of the wood, magnifying knots and cracks with a special wood filler in your choice of 3 colors. Available in unlimited custom colors, lengths up to an impressive 39', and chevron or herringbone patterns.

COMPOSITION

Engineered hardwood planks consisting of WBP exterior-grade birch plywood and a European oak plank top layer, glued together with adhesives in accordance with E1 European standards similar to CARB2.

STANDARD DIMENSIONS

Total thickness (mm)	13 mm (½") - 16 mm (5/8")
Top Layer thickness (mm)	±4 mm (nominal)
Plywood thickness (mm)	9 mm (.35") - 12 mm (.47")
Standard Length (ft)	5.9' - 8.1' (max 10% shorter lengths)
Custom Length (ft)	Up to 39' (room length)
Width (in)	7.08" - 8.66" - 14.17"

GRADE OPTIONS

	Prime	Prime B	Natural AB	Natural ABC	Rustic	Rustic Plus
Knots	Rare (max .4")	Few (max .75")	Filled (max 1.1")	Filled (max 2")	Filled (max 2")	Any size
Cracks	None	None	None	Few	Yes	Yes
Sapwood	No	No	No	No	No	No

COLOR VARIATION

Reactive stains produce unique and rich tones by interacting with the natural tannins in wood. This inherent process leads to color variations in each plank, as their individual tannin levels contribute to the distinct outcome.

ESSENTIAL PROPERTIES

Finish	Titanium
Formaldehyde emission	E1 - CARB2 compliant
Janka Hardness	1120 lbf (4980N)
Thermal conductivity	0.079 m2 K/W
Fire Reaction	Dfl-S1
Profile	Tongue & Groove, micro bevel on long sides
Warranty & Maintenance	www.hauteplank.com
Lead time	12-16 weeks

GENERAL FEATURES

- Suitable for underfloor heating
- Herringbone and chevron patterns available
- Custom color-matching upon request